

**WHAT IS CLAIMED IS:**

1. A method of anti-pollution for exhaust, comprising the following steps:

(1) providing a closed housing filled with a plurality of filter materials and a plurality of clearances being between the filter materials;

(2) connecting a discharge part of the exhaust to a hole at an end of the closed housing and another hole at another end of the closed housing for leading treated exhaust out; and

(3) introducing the exhaust into the closed housing and a plurality of contaminating particles in the exhaust being left in the closed housing and the treated exhaust being capable of reducing original pollution thereof after being led out from the closed housing.

2. The method of anti-pollution for exhaust according to claim 1, wherein the housing can have a single space or can be separated into two or more communicating rooms with one or more partitions being added.

3. The method of anti-pollution for exhaust according claim 1, wherein an interior of the housing can be formed with a plurality of separated zones by way of intervening with a plurality of grids and each of the separated zones can be added with the filter materials.

4. The method of anti-pollution for exhaust according claim 1, wherein the filter materials are a plurality of filtering particles, which can be formed with different shapes, and the filtering particles can be made of one or more of metal, fiber, stone, pottery, porcelain, ceramics, resin and cotton.

5. The method of anti-pollution for exhaust according claim 1, wherein the housing can be added with a relief valve for relieving an excessive pressure and/or a temperature controller for a temperature reduction.

6. The method of anti-pollution for exhaust according claim 1, wherein the filter material on a surface thereof can be added with catalyst convert agent.

7. An anti-pollution device for exhaust, comprises  
a housing, providing an inner filtering chamber;  
an inlet hole, being provided on the housing to communicate the filtering  
chamber;  
5 an outlet hole, being provided at the filtering chamber of the housing to  
communicate with a wall of the housing;  
a plurality of filter materials, being congregated and filled in the housing  
with a plurality of clearances between the filter materials;  
whereby, once the inlet hole connects with a discharge port for the  
10 exhaust, a plurality of contaminating particle in the exhaust can stay in the  
filtering chamber while the exhaust passes through the filtering chamber so  
that the exhaust may reduce the pollution to the environment.
8. The anti-pollution device for exhaust according to claim 7, wherein the inlet  
hole and the outlet hole can extend a distance of pipe section respectively.
- 15 9. The anti-pollution device for exhaust according to claim 7, wherein the  
housing can be added with a relief valve for reliving an excessive pressure  
and/or a temperature controller for a temperature reduction.
10. The anti-pollution device for exhaust according to claim 7, wherein a muffler  
can be added to the housing.
- 20 11. The anti-pollution device for exhaust according to claim 7, wherein an agitator  
and/or a ash blow device can be added into the housing.
12. The anti-pollution device for exhaust according to claim 7, wherein the filter  
materials are a plurality of filtering particles, which can be formed with  
different shapes, and the filtering particles can be made of one or more of  
25 metal, fiber, stone, pottery, porcelain, ceramics, resin and cotton.
13. The anti-pollution device for exhaust according to claim 7, wherein the  
filtering chamber can be formed with two or more rooms by way of a or more

10066831.030402

partitions with each of the rooms being filled with the filter materials and a passage communicates with the rooms.

14. The anti-pollution device for exhaust according to claim 13, wherein each of the partitions can be a box net with grids.

10066881-030402  
20190918 0900